Cable and lifting accessories Zinc-plated

Trawling D-Shackle

Square Head

Available from 16/20 mm

to 22/25 mm

W.L.L: up to 6.500 Kg

TURNBUCKLES



Available from M5 to M36

W.L.L: up to 2.665 Kg

DIN 1480 Turnbuckle Jaw/Eye

W.L.L: up to 3.000 Kg

DIN 1478 Closed Body

Turnbuckle Eye/Eye

W.L.L: up to 8.665 Kg



DIN 1480 Turnbuckle Eye/Eye W.L.L: up to 8.665 Kg



W.L.L: up to 2.665 Kg







DIN 1480 Turnbuckle Jaw/Jaw Available from M6 to M36 W.L.L: up to 7.165 Kg

DIN 1480 Turnbuckle Welding Rod Available from M6 to M38 W.L.L: up to 11.300 Kg

DIN 1478 Closed Body Turnbuckle Hook/Eye Available from M5 to M36 W.L.L: up to 2.665 Kg








DIN 1478 Closed Body

Hook for DIN 1480 Turnbuckle



Welding Rod Threaded End

W.L.L: up to 2.300 Kg



DIN 1480 Turnbuckle Body


W.L.L: up to 2.300 Kg

Turnbuckle Jaw/Jaw

Available from M5 to M36

W.L.L: up to 7.165 Kg













W.L.L: up to 80 Kg

Wire Stretcher Available from 80x26 mm to 104x26 mm

Turnbuckle W.L.L: up to 2.900 Kg

Eye Bolt for DIN 1480



Oval Lifting Eye

W.L.L: up to 5.000 Kg



DIN 580 Lifting Eye Bolt W.L.L: up to 8.600 Kg



DIN 580 Lifting Eye Nut W.L.L: up to 8.600 Kg

These products are not PPE (Personal Protection Equipment) *Contact us for more information on our stainless steel rigging hardware range

SHACKLES



D-Shackle

W.L.L: up to 20.000 Kg


D-Shackle Square Head

W.L.L: up to 2.100 Kg

Available from 5 mm to 25 mm









Trawling D-Shackle Socket Head Available from 20/22 mm to 25/28 mm W.L.L: up to 5.000 Kg

HEAVY-DUTY SHACKLES

W.L.L: up to 3.600 Kg







D-Shackle **Heavy-Duty** W.L.L: up to 25.000 Kg



Bow Shackle Heavy-Duty W.L.L: up to 6.500 Kg

Wire Rope Clip U.S Type



D-Shackle **Heavy-Duty** with Nut Available from 5 mm to 19 mm W.L.L: up to 4.750 Kg



Bow Shackle Heavy-Duty with Nut Available from 5 mm to 19 mm W.L.L: up to 4.750 Kg

WIRE ROPE CLIPS



These products are not PPE (Personal Protection Equipment)

*Contact us for more information on our stainless steel rigging hardware range

DIN 741 Wire Rope Clip

Available from Ø 2 to Ø 50



Simplex Wire Rope Clip



Duplex Wire Rope Clip



Egg-Shaped Wire Rope Clip Available from Ø 2 to Ø 6

QUICK LINK, DIN 5299, WELDED RING AND S-HOOK.



DIN 5299 Available from 4x40 mm to 15x200 mm W.L.L: up to 650 Kg



DIN 5299 with Safety Latch to 12x140 mm W.L.L: up to 450 Kg





Available from 3 mm to 10 mm W.L.L: up to 180 Kg



Available from 3 mm to 10 mm W.L.L: up to 180 Kg

WIRE ROPE THIMBLES



DIN 6899/A Wire Rope Thimbles



Round Wire Rope Thimbles Available from Ø 12 to Ø 18

STEEL, ALLOY AND GRADE 80 LIFTING HOOKS





Grade 80 Clevis

Self-Locking Hook

1.200 Kg to 8.000 Kg



Carbon Steel / Alloy Steel Liftina Hook with Safety Latch 750 Kg to 7.000 Kg



Swivel Hook with

Safety Latch

W.L.L available from

1.000 Kg to 5.300 Kg



Grade 80 Swivel Self-Locking Hook 1.120 Kg to 8.000 Kg

Self-Locking Hook W.I.I. available from 1.120 Kg to 8.000 Kg



Master Link Assembly

2.360 Kg to 11.200 Kg

W.L.L available from



Cable Connector

1.120 KG to 8.000 Kg

Oblong Master Link

1.600 Kg to 8.000 Kg

These products are not PPE (Personal Protection Equipment) *Contact us for more information on our stainless steel rigging hardware range







Cable and lifting accessories

Zinc-plated

Our commitment to quality and the environment

ISO 9001:2015

We aim to keep our customers informed at all times, ensuring an efficient communication flow. We also undertake to treat our customers with the utmost respect and to apply continuous improvement to our customer service processes.





ISO 14001:2015

Our goal is to work in harmony with the environment and to respect the current legislation. We also undertake to integrate environmental awareness into the processes of our



Uniq Quality The 7 points







Homogeneity of

Compliance with the requirements of the certification




A brand supported by



Commercial proximity Personalized counseling



Very complete range of products







JIN 360° Safety

